

Reflexbond XL

Reinforced and repositionable adhesive aluminum tape.



KEY STRENGTHS

- Can be cut by hand
- Very high reflectivity (95%)
- Applicable in wet conditions
- Repositionnable
- Reinforced with glass cloth
- High adhesive strength

Reinforced and repositionable adhesive aluminum tape.

GENERAL CHARACTERISTICS :

Material	Protector made of siliconised paper, adhesive mass and reinforced aluminium film	
Thickness	0,2 mm	
Mass per unit area	210 g/m ²	

MECANICAL CHARACTERISTICS :

Watertightness	W1	EN 1928
Sd Value	> 1500 m	EN 1931

MAXIMUM PEEL RESISTANCE :

with Skytech Pro XL substrate	43 N/25mm	EN 12316-2
with Skytech Pro XL substrate after	64 N/25mm	EN 12316-2

RESISTANCE TO TEARING :

Shear resistance	1087 N	EN 12317-2
Shear resistance after ageing	1027 N	EN 12317-2

FIRE CHARACTERISTICS :

Reaction to fire , System with max. 10% tape*	A2-s1,d0	EN 13501-1
---	----------	------------

*substrates : Skytech Pro XL or A2 Firebreather W1

PACKAGING CHARACTERISTICS :

Width	75/100/125 mm
Length	25 m
Rolls / box	16/12/12 rolls/box

Storage: +5°C to +40°C temperature. 50 – 60 % relative humidity recommended.

Please keep the rolls with the original packaging and do not leave the roll tape pallets in the dry place. Application temperature: from +5°C (lower temperatures not yet tested).

Service temperature after installation: -30°C to +90°C

Customers are responsible for their own product tests, evaluation and safety procedures.

Ref. 75 mm : 00475
Ref. 125 mm : 00479
Ref. 100 mm : 00486