

Reflexbond XL

Reinforced and repositionable adhesive aluminum tape.



KEY STRENGTHS

- Can be cut by hand
- Very high reflectivity (95%)
- Applicable in wet conditions
- Repositionable
- Reinforced with glass cloth
- High adhesive strength

Reflexbond XL

Reinforced and repositionable adhesive aluminum tape.

TECHNICAL DATAS

Material	Protector made of siliconised paper Adhesive mass Reinforced aluminium film
Width	75 / 100 / 125 mm
Length	25 m
Temperature resistance	-40°C to +90°C
Application temperature	min. - 10°C
Emissivity/ Reflectivity	5 % / 95 %
Roll weight	0,6 / 0,8 / 1 kg
Packaging	75 mm : 16 rolls / box 100 mm : 12 rolls / box 125 mm : 12 rolls / box



BENEFITS

- Repositionable product before marouflage
- Can be easily cut manually and without any tool
- UV resistant
- Applicable in wet conditions
- Reinforced with glass fabric
- Unique on the market

The only adhesive approved by the Technical Advice SKYTECH PRO XL 20/16-370_V2.

INSTALLATION AND SUBSTRATES

Materials

- Concrete
- Dry wood
- Brick

Membranes

- Non-combustible and reflective rainscreens
- Standard roof membranes
- Vapour control layer
- Multilayer membranes
- Insulation overlaid with kraft or aluminium

FIELD OF APPLICATION

- Reinforced adhesive foil for reflective insulation and the treatment of singular points (chimney ducts, roof windows, valleys..).

STORAGE

- Keep away from cold and heat.

