

Firetape 340B

Black fire retardant adhesive tape.



KEY STRENGTHS

- High UV resistance
- Reinforced with glass cloth
- Easy to install
- High resistance to tearing

Firetape 340B

Black fire retardant adhesive tape.

GENERAL CHARACTERISTICS :

Material	Protector made of siliconised paper, adhesive mass and glass cloth
Thickness	0,34 mm
Mass per unit area	340 g/m ²

MECHANICAL CHARACTERISTICS :

TENSILE STRENGTH :

Longitudinal sense (L)	4 200 N/50mm	EN 12311-1
Transversal sense (T)	3 100 N/50mm	EN 12311-1

RESISTANCE TO TEARING :

Longitudinal sense (L)	290 N	EN 12310-1
Transversal sense (T)	390 N	EN 12310-1

ELONGATION :

Longitudinal sense (L)	6%	EN 12311-1
Transversal sense (T)	5 %	EN 12311-1

PEELING RESISTANCE :

After 72h	20 N/50mm ⁽¹⁾	EN 12316-2
-----------	--------------------------	------------

⁽¹⁾ cohesive failure

FIRE CHARACTERISTICS :

System with max. 10% tape ⁽²⁾	A2-s1,d0	EN 13501-1
--	----------	------------

⁽²⁾ substrates : BLACK A2 Firebreather W2

PACKAGING CHARACTERISTICS :

Width	75 mm
Length	25 m
Rolls / box	16 rolls/box

Storage: +5°C to +40°C temperature. 50 – 60 % relative humidity recommended.

Please keep the rolls with the original packaging and do not leave the roll tape pallets in the dry place.

Application temperature: from +5°C (lower temperatures not yet tested).

Service temperature after installation: -30°C to +90°C

Customers are responsible for their own product tests, evaluation and safety procedures.

Ref. 00576